




RP60 USB 3.2 Gen 2x2 Portable SSD



High Speed File Transfer

Read speeds up to 2,000MB/s* and write speeds up to 1,800MB/s*



Dust and Water-Proof

Protect your data from the elements



USB 3.2 Gen 2x2

USB 3.2 Gen 2x2 connectivity backward compatible with USB 3.2 Gen 2x1, USB 3.2 Gen 1, USB 2.0 and USB 1.1

RP60 Rugged Portable SSD

The RP60 USB 3.2 Gen 2x2 Type-C Rugged Portable SSD is the next generation in mobile storage, boasting not only increased storage capacity and speeds, but also exceptional durability against the elements. Featuring a 3.2 Gen 2x2 Type-C interface with read and write speeds up to 2,000 MB/s and 1,800 MB/s respectively*. It's designed to be a mobile storage solution superior to previous generations.

The RP60 USB 3.2 Gen 2x2 Type-C Rugged Portable SSD is certified dust & waterproof – qualified with an IP65 rating*. Save your photos, documents, and videos anywhere and anytime.

The RP60 USB 3.2 Gen 2x2 Type-C Rugged Portable SSD features a simple design to fit any situation. A rubberized housing offers increased grip, making it the perfect solution for life on the go.

FEATURES AND BENEFITS

- Performance of up to 2,000 MB/s seq. read and 1,800 MB/s seq. write
- IP65 Dust and Water Resistance
- Low power consumption
- USB 3.2 Gen 2x2 connectivity, backwards compatible with USB 3.0, USB 2.0
- Compatible with Windows, Mac OS X and Linux Kernel

*Consistent with IP65 rating, tested under controlled conditions: water flow of 100kPa for 3 minutes. Water resistant capabilities may vary depending on the actual conditions. 2kg/m³ of active dust with a pressure under 2kPa for 8 hours. Dust resistant capabilities may vary depending on the actual conditions.

PRODUCT SPECIFICATIONS

Interface	USB 3.2 Gen 2x2; Backwards compatible with USB 3.2 Gen 2x1, USB 3.2 Gen 1, USB 2.0 and USB 1.1
Form Factor	Portable

PERFORMANCE (MAX SEQUENTIAL READ/WRITE)

1TB	2,000MB/s(Read) 1,800MB/s(Write)
2TB	2,000MB/s(Read) 1,800MB/s(Write)

ENVIRONMENTAL

Operating Temperature	0°C ~ 70°C
Storage Temperature	-25 °C ~ 85 °C
Certifications	CE, FCC, EMC, ROHS, REACH, UKCA

COMPATIBILITY

Operating Systems	Window 11, Windows 10, Windows 8.1, Windows 7, Vista, XP, Mac OS 10.3 or later version, Linux Kernels 2.5 and above
-------------------	---

ADDITIONAL FEATURES

Service & Support	3-Year Limited Warranty or TBW**
-------------------	----------------------------------

PRODUCT INFORMATION

Usable Capacities (IDEMA)	1TB, 2TB
PNY Part Number	1TB : PSD0CS3060-1TB-RB 2TB : PSD0CS3060-2TB-RB
UPC	1TB : 751492787541 2TB : 751492787558
EAN	1TB : 4718006456887 2TB : 4718006456894
Accessory	USB Type-C to C cable
Package Dimensions	100 x 130.3 x 32 mm
Dimensions (L x W x H)	100 x 60.3 x 12.4 mm
Weight	100 g

*Sequential read and write data transfer rates based on PNY internal testing. Performance may differ depending upon host device
**For full details visit www.pny.com